

10018115 DE 1999

JC09 Rec'd PCT/PTO 7 4 DEC 2001

BAKER BOTTS LLP TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35.U.S.C. 371		EXPRESS MAIL LABEL No. EF377397961US	DATE 14 DECEMBER 2001
		ATTORNEY'S DOCKET NO A34885 PCT USA	
		U.S. APPLICATION NO. 10/018115	
INTERNATIONAL APPLICATION NO PCT/NL00/00411	INTERNATIONAL FILING DATE 14 JUNE 2000	PRIORITY DATE CLAIMED 14 JUNE 1999	
TITLE OF INVENTION PLANT SUPPORT AND METHOD FOR MANUFACTURING SUCH PLANT SUPPORT			
APPLICANT(S) FOR DO/EO/US HENRICUS WILHELMUS THEODORUS JANSSEN			
<p>Applicant herewith submits to the United States Designated /Elected Office (DO/EO/US) the following items and other information:</p> <ol style="list-style-type: none"> <input checked="" type="checkbox"/> This is a FIRST submission of items concerning a filing under 35 U.S.C. 371. <input type="checkbox"/> This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. 371. <input checked="" type="checkbox"/> This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(I). <input type="checkbox"/> A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date. <input type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371(c)(2)) <ol style="list-style-type: none"> <input type="checkbox"/> is transmitted herewith (required only if not transmitted by the International Bureau). <input type="checkbox"/> has been transmitted by the International Bureau. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US). <input checked="" type="checkbox"/> A translation of the International Application into English (35 U.S.C. 371(c)(2)). <input checked="" type="checkbox"/> A copy of the International Search Report (PCT/ISA/210) <ol style="list-style-type: none"> <input checked="" type="checkbox"/> are transmitted herewith (required only if not transmitted by the International Bureau). <input type="checkbox"/> have been transmitted by the International Bureau <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired. <input type="checkbox"/> have not been made and will not be made. <input type="checkbox"/> A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)). <input type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)). <input type="checkbox"/> A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)). <p>Items 11. to 16. below concern other document(s) or information included:</p> <ol style="list-style-type: none"> <input checked="" type="checkbox"/> A copy of the International Preliminary Examination Report (PCT/IPEA/409) <input type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included. <input type="checkbox"/> A FIRST preliminary amendment. <input type="checkbox"/> A SECOND or SUBSEQUENT preliminary amendment. <input type="checkbox"/> A substitute specification. <input type="checkbox"/> A change of power of attorney and/or address letter. <input checked="" type="checkbox"/> Other items or information: <ol style="list-style-type: none"> <input checked="" type="checkbox"/> a copy of the International Search Report (PCT/ISA/210) <input checked="" type="checkbox"/> a copy of the International Preliminary Examination Report (PCT/IPEA/409) <p>ALSO: Form PCT/IPEA/416 International Published application with amended sheets including 18 PAGES SPECIFICATION, 3 SHEETS OF CLAIMS, 7 SHEETS DRAWINGS</p>			

10018115

JC13 Rec'd PCT/PTO 14 DEC 2001

INTERNATIONAL APPLICATION NO PCT/NL00/00411		INTERNATIONAL FILING DATE 14 JUNE 2000		PRIORITY DATE CLAIMED 14 JUNE 1999	
17. <input checked="" type="checkbox"/> The following fees are submitted: Basic National Fee (37 CFR 1.492(a)(1)-(5): Neither international preliminary examination fee (37 CFR 1.482) Nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO (1.492(a)(3)) \$1,040 International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO (1.492(a)(5)) \$890.00 International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO (1.492(a)(2)) \$740.00 International preliminary examination fee paid to USPTO (37 CFR 1.482) but all claims did not satisfy provisions of PCT Article 33(1)-(4) (1.492(a)(1)) \$710.00 International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(1)-(4) \$100.00 ENTER APPROPRIATE BASIC FEE AMOUNT =				CALCULATIONS <small>PTO USE ONLY</small> 	
				= \$ 890	
Surcharge of \$130.00 for furnishing the oath or declaration later than [] 20 [] 30 months from the earliest claimed priority date (37 C.F.R. 1.492(e)).				\$	
Claims	Number Filed	Number Extra	Rate	\$	
Total Claims	26 -20=	6	X \$ 18.00	\$	108
Independent Claims	4 -3=	1	X \$ 84.00	\$	84
Multiple dependent claim(s) (if applicable)			+ \$280.00	\$	280
TOTAL OF ABOVE CALCULATIONS =				\$	1,362
Reduction by 1/2 for filing by small entity, if applicable.				\$	
SUBTOTAL =				\$	1,362
Processing fee of \$130.00 for furnishing the English translation later than [] 20 [] 30 months from the earliest claimed priority date (37 CFR 1.492(f)). +				\$	
TOTAL NATIONAL FEE =				\$	1,362
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property +				\$	
TOTAL FEES ENCLOSED =				\$	1,362
				Amt. refunded	\$
				charged	\$
a. <input checked="" type="checkbox"/> A check in the amount of \$ 1362 to cover the above fees is enclosed. b. [] Please charge our Deposit Account No. 02-4377 in amount of \$ to cover the above fees. A copy of this sheet is enclosed. c. <input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 02-4377. A copy of this sheet is enclosed. NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status. SEND ALL CORRESPONDENCE TO: RICHARD G. BERKLEY BAKER BOTTS L.L.P. 30 Rockefeller Plaza New York, New York 10112-4498					
Attorney: RICHARD G. BERKLEY				PTO Reg: 25,465 14 DECEMBER 2001 Date	

10018115 10/018115

JG13 Rec'd PCT/PTO 14 DEC 2001

BAKER BOTTS LLP

Attorney Docket Number: A34885 PCT USA

Title: PLANT SUPPORT AND METHOD FOR MANUFACTURING SUCH PLANT SUPPORT

Use Space Below for Additional Information:

AVC 00/76295

New page 1

EPO - DG

30. 05. JC
200

JC1
2007

10/018115

NL 000000411

JC13 Rec'd PCT/PTO
PCT/NL00/00411

14 DEC 2001

(54)

Title: Plant support and method for manufacturing such plant support.

The invention relates to a method for manufacturing a plant support according to the preamble of claim 1. Such method is known from US 5,311,700.

In this known method a container is provided, manufactured of wire mesh, which is layered on the inside with water permeable, non-biodegradable polyurethane. Roots of plants growing inside said container can grow through said polyurethane and will form thin air roots outside said foil. The plants, such as trees, can be planted together with said container and liner.

NL 8700470 discloses a method for planting using a combined holder
10 and support. In this method a container is used made of wire mesh, closed on
the upper side. In this container a growing medium, such as earth is
introduced, in which plants are grown in a position away from the position in
which the container is to be finally used. The container can only be moved
together with the growing medium when said plants have rooted sufficiently
15 to hold together said growing medium. No indication for use of a covering
material is given in this publication.

From practice, plant supports are known in the form of plastic boxes having a closed bottom and sidewall. In these boxes, soil or another growth medium is poured wherein a plant is placed, which plant is raised in this box. For that matter, "plant" should in this context be understood to include at least a plant, tree, shrub or the like. During raising of the plant in question, the roots thereof will grow against the wall and bottom of the pot and, upon further growth, will extend along the inside of the wall. When the plant has been raised sufficiently, it is removed from the pot, together with the ball formed in the pot, and is dug in in a soil suitable therefor, in which the plant is to be further cultivated. Because the roots in the pot have grown along the wall, it will take a relatively long time, after transplanting, before the roots

New page 1a

will spread in the surrounding soil. This means that further growth is at least temporarily impeded, while, moreover, the relevant plant will fix itself in the soil only after a relatively long time. This is particularly disadvantageous when relatively large plants are to be transplanted, because at least initially, 5 these plants will have insufficient stability. A further drawback of these known pots is that the plant with the ball should be taken out of the pot, after which the pot should be removed. This is labor-intensive, relatively costly and, moreover, environmentally burdensome.

It has already been proposed to manufacture pots from reed or peat 10 dust, which pots have been pressed. Such pots have as a drawback that they are of weak construction, while moreover, to these pots it likewise applies that the roots will grow on the inside along the wall. Moreover, the storage lives of such pots is relatively short, which means that plants cultivated therein should be transplanted relatively quickly, because otherwise the pot will have 15 decomposed so far that it will no longer have any constructional firmness

WO 00/76295

2

PCT/NL00/00411

whatsoever and the roots will already have grown so far that the plant can no longer be transplanted without damage.

The object of the invention is to provide a method for manufacturing a plant support of the type described in the preamble, which method results in a
5 plant support wherein the drawbacks of the known plant supports are avoided, while the advantages thereof are maintained. To that end, a method according to the invention is characterized by the features of claim 1.

In a method according to the invention, a box-shaped element is used having a relatively open wall structure, such that in principle, soil could fall
10 therethrough while roots could grow without any obstruction to the outside through said relatively open structure. According to the invention, this box-shaped element is lined such that said partially open wall is covered at least partially, allowing soil or a like growth medium to be easily introduced into the box-shaped element without possibly passing outside through said
15 openings. Preferably, this involves the use of a covering material which is substantially biodegradable and has such a structure that soil, at least the comparable growth medium to be applied, cannot pass through, while roots of a plant to be cultivated in the relevant growth medium can easily grow through the relevant covering material and the above-mentioned openings.
20 Thus, a plant support is obtained which can readily be placed in or on the soil, such that the roots can grow through the covering material to the outside of the box-shaped element and into the surrounding soil for anchoring the plant and, during further cultivation, for supplying the required growth substances. Preferably, the box-shaped element, during use, is at least largely dug in in
25 said soil.

With a plant support manufactured according to this method, plants can be cultivated in a simple manner, while the plant support can be disposed entirely above the ground. Roots will grow at least partially into the covering material, in a direction enclosing an angle other than 180 degrees with the
30 relevant part of the wall of the pot, for instance substantially at right angles

WO 00/76295

3

PCT/NL00/00411

thereto. When the roots, in particular relatively small roots such as the root hairs, pass through the covering material, they come within the reach of (day)light, as a result of which the growth will brake or even stop at least for the time being. When the plant support is subsequently dug in in the ground at least partially, the roots, then extending under the ground, will grow further, so that a good anchoring and nutrition becomes possible. During the cultivation of the plant, the box-shaped element will provide for sufficient constructional strength of the plant support, so that it can be picked up and displaced in a simple manner. To this end, the plant support offers sufficient handling possibilities, while the plant support can moreover be secured to the ground in a relatively simple manner by means of the box-shaped element. When, during use, the plant support is dug in in the ground only partially, the parts projecting from the ground can easily be covered for embellishing the appearance and closing off the partially open wall parts. However, the plant support may also be used uncovered.

In an advantageous embodiment, a method according to the invention is further characterized by the features of claim 2.

By manufacturing the box-shaped element from a mesh-shaped material, sufficient bearing capacity and support of the covering material can readily be obtained, while, moreover, a sufficiently open structure of the wall is maintained. By using the mesh-shaped structure for both the wall and the bottom of a box-shaped element, it is moreover provided that roots can also grow through the bottom of the box-shaped element. During raising of the plant up to its transplantation, the box-shaped element can then simply be placed on a closed base or disposed such that also the bottom side of the box-shaped element comes into contact with daylight, to prevent continued growth of the roots.

Further, a method according to the present invention is preferably characterized by the features of claim 4.

WO 00/76295

4

PCT/NL00/00411

The use of natural materials, in particular natural fibers and binding agent, offers the advantage that a particularly environmentally friendly plant support is obtained. Preferably, in a method according to the invention, coco fibers and binding agent such as latex are used, while simply through a
5 suitable choice of the dimensions of the coco fibers, the type of binding agent and the ratio thereof, covering material can be obtained of different degrees of open structure and time that this structure is maintained, so that in each case, a suitable covering material can be chosen, for instance depending on the plant to be cultivated, the expected period from raising to transplanting and the like.

10 In further elaboration, a method according to the invention is further characterized by the features of claim 8.

The use of at least one substantially vertically extending guide element in a plant support according to the present invention offers the advantage that during use, plants cultivated in the plant support can readily
15 be guided along the guide element, for support thereof. Because the guide element is secured in or to the box-shaped element or forms an integral part thereof, the additional advantage achieved is that the guide element is readily kept in the desired position without further necessitating trestles or like measures. Indeed, sufficient anchoring of the box-shaped element or at least
20 the plant in the soil, after transplantation, will provide for sufficient stability of the guide element.

The invention further relates to a method for cultivating plants and the like, characterized by the features of claim 9.

Such method offers the advantage that in a particularly simple
25 manner, plants or the like can be cultivated in a first position, whereafter the plants together with the plant support can be picked up and displaced into an operating position, wherein the plant support can, for instance, be secured in or to the ground, be dug in entirely or partially or put down on the ground. This means that for consumers, at least end users, relatively full-grown plants
30 become available relatively quickly.

WO 00/76295

5

PCT/NL00/00411

The invention further relates to a method for manufacturing a hedge, characterized by the features of claim 13.

With a method according to the present invention, loose hedge elements can be manufactured with guidable, relatively fast-growing plants, so that relatively quickly, a substantially closed surface can be obtained. This means that for a user, a hedge forming a suitable separation can be obtained in a relatively fast manner. Moreover, hedge elements can thus be obtained from plants which are normally not directly suitable for forming a hedge, because these plants cannot, or at least not without any problem, grow to the desired height independently.

Through the use of box-shaped elements with guide elements connected thereto, the advantage achieved is that the entirely or partially full-grown hedge elements can readily be picked up and displaced. Thus, for instance hedge elements can be positioned and prepared as prefab elements on a suitable location, such as in a greenhouse or at an agricultural or horticultural farm, to obtain the desired hedge elements with substantially closed plant surface, whereafter the relevant hedge elements can be picked up and displaced to the position where they are to be used, for instance a garden, park, exhibition or the like. The advantage thus achieved is that an end user directly disposes of a hedge, or at least a hedge element, which is full-grown such that the desired separation is obtained. The box-shaped element provides that the entire hedge element can be picked up at once, including the relevant plants and the associated roots. This simply prevents the plants from being adversely affected by the displacement.

By linking a series of hedge elements formed according to the invention, a hedge of relatively great length can be obtained.

The invention further relates to a plant support, characterized by the features of claim 16.

Such plant support offers the advantage that it has a relatively simple structure, that it can be of a constructionally stable design and can readily be

WO 00/76295

6

PCT/NL00/00411

used for cultivating plants which are to be displaced in course of time, while after displacement, the roots of the relevant plant will easily provide for anchoring in the ground.

In a particularly advantageous embodiment, a plant support according
5 to the invention is further characterized by the features of claim 22.

A demountable or at least modular design of the plant support offers the advantage that the plant support can be transported in parts, at least prior to use, so that less transport volume is required. Moreover, a plant support can thus be simpler to handle. Prior to use, the desired plant support can then be assembled from the modules supplied. Such plant support moreover offers the advantage that with a limited number of different parts, a large number of plant supports, possibly of different shapes and dimensions, can be built up, which is advantageous in terms of production.

In the further subclaims, further embodiments of a method and plant
15 support according to the invention are described.

To clarify the invention, exemplary embodiments of a method and plant support according to the present invention will be further explained hereinafter, with reference to the accompanying drawings. In these drawings:

Fig. 1 is a front view of a box-shaped element with guide element
20 according to the invention:

Figs. 2A-2C are side elevations of three alternative embodiments of a box-shaped element with guide element according to Fig. 1;

Fig. 3 is a perspective view of three juxtaposed hedge elements according to the invention:

25 Fig. 4 is a sectional side elevation of a portion of a plant support according to the invention, in a simple embodiment;

Fig. 5 shows a plant support according to Fig. 4 during the raising of a plant, in particular a tree;

Fig. 6 shows a plant support according to Fig. 5, after transplantation:



WO 00/76295

7

PCT/NL00/00411

Fig. 7 shows a plant support with guide element, in two demountable embodiments;

Fig. 8 is a top plan view of a plant support according to Figs. 1-3, in an alternative embodiment;

5 Fig. 9 shows a plant support according to the invention in a further alternative embodiment; and

Fig. 10 is a side elevation of a noise protection wall built up with elements according to the invention.

10 In this specification, identical or corresponding parts have identical or corresponding reference numerals. In the embodiments shown, the invention is described with reference to, inter alia, guide plants such as ivy and trees, yet it will be understood that in a method according to the present invention, use can also be made of other sorts of plants, shrubs and trees, both single and in rows or groups.

15 Fig. 1 is a front view of a box-shaped element 1 with guide element 2, manufactured from wire metal, such as, for instance, woven reinforcing steel rods, to obtain a mesh-shaped structure having substantially rectangular
20 openings 4 between upright wires 6 and horizontal wires 8. It will be understood that similarly, other structures can be used as well, as long as at least the wall 12 and/or the bottom 14 of the box-shaped element 1 at least partially have an open structure, while in this embodiment, it is advantageous when along the guide element 2, plants can be guided or possibly secured thereto, in a manner known per se from gardening. It will be understood that the box-shaped element 1 may be manufactured in the same or a similar
25 manner, from the same material, as the guide element 2. In this specification, at least with regard to Figs. 1-3, the assembly of a box-shaped element 1 with guide elements 2 will further be referred to as plant support 10.

Fig. 2A shows a plant support 10 in a first embodiment, in side elevation, with the plant support 10 manufactured in one piece. To that end, a
30 box-shaped element 1 is formed from flat-woven reinforced iron rods by

WO 00/76295

8

PCT/NL00/00411

bending the metal, to form two longitudinal walls 12 and a bottom 14. From the upper longitudinal edge of one of the sidewalls 12, parallel to this longitudinal wall 12, a second wall face 16 extends to a position adjacent the bottom, to which a second bottom face 18 connects, extending parallel to the bottom 14 to a position near the center thereof. From the side of the second bottom face 18 remote from the longitudinal wall 12, the guide element 2 then extends vertically. Hence, in such embodiment, the guide element 2 is fixedly connected to the box-shaped element 1, so that a stable, relatively rigid construction is formed and the guide element is simply prevented from becoming detached from the box-shaped element 1.

Fig. 2B is a side elevation of an alternative embodiment of a plant support 110 according to the invention, the box-shaped element 101 being manufactured separately, for instance by bending woven wire metal, to form a bottom 114 and sidewalls 112. The lower end of a guide element 102 formed from woven metal wire has been bent over at right angles to form a second bottom face 118. The second bottom face 118 has a width that is approximately equal to half the width of the bottom 114. For instance by welding, clamping means or the like, the second bottom face 118 is secured to the bottom 114 with its free longitudinal edge connecting to one of the longitudinal walls 112, to realize a stable positioning of the guide element 102 in the box-shaped element 101.

Fig. 2C shows an embodiment of a plant support 10 comparable with the embodiment shown in Fig. 2A, however with the second wall face 16 left out. The second bottom face 18 extends approximately horizontally, at least parallel to the bottom 14, from the upper longitudinal edge of one of the longitudinal walls 12, with the guide element 2 again extending at right angles from the side of the second bottom face 18 remote from the longitudinal wall 12. Such embodiment of a plant support 10 is simpler to manufacture in one piece. However, an embodiment according to Fig. 2A has the advantage

WO 00/76295

9

PCT/NL00/00411

that the box-shaped element 1 is entirely clear at its top side, on two sides of the guide element 2.

A plant support 10, 110 according to the invention can be used as follows.

- 5 The box-shaped element 1, 101 is covered with a covering material 20, for instance on the inside, as shown in Fig. 2C and Figs. 4-6. In Figs. 2A and 2B, this covering material 20 has been left out for clarity's sake. Preferably, as covering material 20, a biodegradable sheet or film-shaped material is used, optionally having a fine mesh structure. Advantageous is the use of natural
- 10 fibers such as ramie, coco or the like, with a natural binding agent, such as latex, starch derivatives or the like added thereto. By pressing slightly, a sheet having the desired, relatively open structure is obtained from said fibers and binding agent, at least such a structure that roots, in particular small roots such as root hairs, can grow into and through the covering material. Through a
- 15 suitable choice of fibers and binding agent, such as coco and latex, a plant support 1 can be obtained which can be disposed above the ground for, for instance, a number of months or even 1-2 years, without its bearing capacity becoming unacceptably low.

- The covering of the box-shaped element 1, 101 is preferably folded
- 20 from a blank, cut from said sheet-shaped material, and pressed in a simple manner on the inside of the box-shaped element. However, strips of covering material may, for instance, also be woven through the meshes of the wall and/or bottom. Other covering manners are, of course, also possible, for instance on the outside or a pressure-molded covering. Next, a growth medium
- 25 122, for instance soil, is poured into the box-shaped element 1, 101, onto the covering material 20. The covering material 20 is of such design that the growth medium cannot fall through the bottom 14, 114 or longitudinal wall 12, 112. As long as the plant support is disposed above the ground, roots 124 of plants 126 inserted into the growth medium are prevented from growing to the
- 30 outside of the box-shaped element 1, 101. The growth is inhibited or even

WO 00/76295

10

PCT/NL00/00411

stopped by (day)light. When the box-shaped element 1 is dug in in the ground, the roots will continue to grow, so that a good anchoring is obtained and the plants will be able to absorb sufficient nutrition from the environment.

As shown in Fig. 2B, plants 126 are placed in the growth medium 122, on both sides of the guide element 102 in the embodiment shown, which plants 126 will grow in a guided manner along the guide element, such that the guide element 2, 102 is covered thereby at least substantially completely. This may involve the use of at least initially fast-growing plants. Thus, a hedge element 128 exhibiting a desired separating action can quickly be obtained.

Fig. 3 is a perspective, schematic view of three adjoining, juxtaposed hedge elements 128. Of each hedge element 128, the box-shaped element 1, 101 has been dug in the ground, shown schematically in Fig. 3 by the line 130. The guide elements 2, 102 extend approximately vertically, with the plants 126 thereagainst to form a substantially closed foliage.

As shown in Fig. 2, a plant support 110 can be disposed with its bottom 114 on a floor 132, for instance in a greenhouse, for the initial growth of the plants 126 therein. When, in the opinion of a user, the plants 126 have grown sufficiently, the relevant hedge element 128 can be picked up from the floor 132 and transferred to, for instance, a garden where the hedge elements 128 can be dug in in the manner shown in Fig. 3, to form the desired hedge.

In the embodiment shown in Fig. 3, a straight hedge is formed with the plant supports 1, 101. However, it will be understood that by means of the hedge elements 128, differently shaped hedges may likewise be obtained. In the embodiment shown in Fig. 1, the plant support 10 is on one side provided with hook elements 34, capable of hooking around an upright 6 of an adjoining plant support 10, to obtain a slightly fixed connection between linked plant supports 10. Moreover, the stability of the various plant supports can thus be increased even further. An additional advantage of a hedge according to the invention is that it can readily be kept at a desired level. Indeed, the hedge, or at least the plants 126, can readily be clipped right above the upper edge 36.

WO 00/76295

11

PCT/NL00/00411

136 of the guide element 2, 102. For that matter, in particular when use is made of climbing plants, these plants will at least substantially not grow above said upper longitudinal edge 36, 136, but fall back against the side of the guide element 2, 102, whereby the height of the hedge element is limited in a natural fashion.

Fig. 4 is a sectional side elevation of a portion of a plant support 210 according to the invention. This plant support 210 comprises a box-shaped element 201, without a guide element in the exemplary embodiment shown. The box-shaped element 201 is built up from a mesh-shaped structure as shown in Fig. 1, with vertical wires 206 and horizontal wires 208. Accordingly, the wall 212 and the bottom 214 have a substantially mesh-shaped, open wall structure. Provided on the inside of the box-shaped element 201 is a covering 220, which is, for instance, folded from a blank or pressed. The covering 220 is manufactured from a covering material composed from substantially natural fibers, in particular coco fibers, ramie fibers or like elongated fibers, and a binding agent, in particular a natural binding agent such as latex, as described earlier with regard to Fig. 2. As appears from the section, the fibers 211 constitute a wall structure which is relatively open but whose openings are much smaller than the meshes in the box-shaped element. The structure of the covering material can readily be selected, for instance on the basis of the desired lifetime and degrading time, the desired porosity and bearing capacity and the like, so that in each case, an optimum plant support can be designed.

Fig. 5 shows the portion of the plant support 210 according to Fig. 4, during the raising of a plant 226, in particular in the form of a tree. However, other plants can of course also be cultivated herein, for instance shrubs such as firethorn or like self-supporting, relatively dense-growing plants capable of forming, for instance, a hedge element. In the embodiment shown in Fig. 5, the plant support 210 is disposed on a bottom face 232, while a growth medium 222 has been poured into the box-shaped element 201. In the growth medium 222, a plant 226 is placed, tended such that a network of roots 224 has been

WO 00/76295

12

PCT/NL00/00411

formed. A number of thinner roots 224 has grown through the covering 220, passing fibers 211, until an end 225 of the relevant roots 224 has reached the side of the covering 220 facing away from the inside of the box-shaped element 210. In that case, the growth stops or is at least inhibited considerably, due to the light into which the roots 224 reach. This readily prevents the roots from growing far outside the plant support 210, while the roots do in fact extend at least partially through the covering 220 in a direction which encloses an angle with the plane of the relevant wall 212 or the bottom 214. Root hairs 227 will grow through the covering 220 as well, while, moreover, a number of root hairs 227 will grow into the covering 220.

After the plant 226 has been raised sufficiently in the plant support 210 in the position shown in Fig. 5, the plant support 210 is picked up together with the plant 226 from the bottom 232 and moved into an operating position, where the plant support 210 at least with the box-shaped element 201 is dug in in the ground 230. Next, the plant 226 is allowed to grow further, while the roots 224 will directly grow on to far outside the box-shaped element 210. The ends 225 of the roots 224 will grow beyond the covering 220, while forming a strongly branched network of roots 224, including root hairs 227, as a result of which the plant 226 will quickly obtain a sufficiently stable anchoring in the ground 230. After a passage of time, the covering 220 will be biodegraded and only the box-shaped element 201 remains behind in the ground, in so far as it will not decompose after a longer passage of time.

As appears from the above description, when a plant support according to the present invention is used, the plant need not be taken from the plant support before it can be transplanted. Because the roots can simply grow through the covering material of the covering 220, they will, after the plant support has been put in the ground at least partially, be able to grow "straight on" simply, unlike the known plant supports, where the roots will be substantially coiled up because of the wall of the pot.

WO 00/76295

13

PCT/NL00/00411

Instead of receiving a plant support 210 in the ground, as shown in Fig. 6, the plant support can also be arranged entirely, at least substantially completely, above the ground, such that substantially only the bottom face 14, 114, 214 is received on or in the ground 130, 230. The roots 224 will then grow
5 into the ground substantially only through the bottom face. By suitable means, such as a tent pegs, ground pins or the like, the box-shaped element can easily be fixed to the ground at least temporarily, while the ground pins can easily engage preferably the horizontal wires. By suitable means, such as plate material, the sidewalls 212 can then be covered, if so desired.

10 Fig. 7 shows, in side elevation, two embodiments of a plant support having a guide element, built up from separate parts. On the left-hand side, a grid-shaped element as described with reference to Fig. 1 is twice bent over at right angles adjacent a lower end thereof, rightwards in Fig. 7, to obtain a guide element 302 having attached thereto a right box element 314R. In the
15 guide element 302, at the level of the box 314R, two slots 303 are provided, extending throughout the width of the guide element 302, by bending over the uprights 306 locally. From a comparable, mesh-shaped material, a second, left box-shaped element 314L is formed by bending over at right angles twice, whose dimensions in the embodiment shown are approximately equal to the
20 right box 314R. In one of the vertical walls of the box-shaped element 314L, there are likewise provided two slotted recesses 303, flush with the slotted recesses in the guide element 302, yet in opposite direction. In the embodiment shown, this is outwards. As appears clearly from Fig. 7, on the left-hand side, when the left box 314L is slid against the guide element 302, an approximately
25 square passage 305 is formed on the side remote from the right box 314R, between the slotted recesses 303. Into each of these passages 305, a bar 307 is inserted, so that the left box-shaped element 314L is secured against the guide element 302. Thus, a particularly stable connection is effected, while transport is readily possible in separate parts.

WO 00/76295

14

PCT/NL00/00411

In Fig. 7, on the right-hand side, an alternative embodiment is shown, wherein a guide element 302 is used which is substantially flat. On either side thereof, a box-shaped element 314L, R is provided, constructed like the left box-shaped element 314L in Fig. 7 as discussed earlier. The two box-shaped elements 314L,R have been slid from both sides against the guide element 302, such that between the slotted recesses 303, the bar element 307 can again be slid, with simultaneous inclusion of the guide element 302. The position of the deformations 303 is chosen so that displacement in vertical direction is not possible, because the deformations 303 abut against horizontal wires 308 of the guide element 302.

It will be understood that other manners of modular construction of an apparatus according to the invention are also possible, for instance through the use of clamping means, screwing means and the like, known per se. Thus, for instance clamping plates can be fixed from either side against box-shaped elements 314 and/or guide elements 302, whereby vertical 306 and/or horizontal wires 308 are clamped. These and many comparable variations will be readily understood by anyone skilled in the art. It is further observed that in Fig. 7 no covering material is shown, for the sake of clarity. However, during use, this covering material will in fact usually be applied.

Fig. 8 is a top plan view of a further advantageous embodiment of a plant support 410 with guide element 402 and box-shaped element 401. The box-shaped element 401 is U-shaped, as for instance shown in Fig. 2b. The longitudinal edges 409 of the guide element 402, which edges are vertical during use, are bent over at right angles in opposite directions relative to the plane of the guide element 402, so that the guide element is slightly Z-shaped in top plan view. On either side, the edges are bent over such that the guide element 402 can be placed in the box-shaped element 401, between the vertical walls 412, with the bent-over portions abutting against said vertical walls 412. By means of, for instance, clamping means, binding means, screw means or the like, or possibly by means of, for instance, welding or gluing techniques,

WO 00/76295

15

PCT/NL00/00411

the bent-over longitudinal edges 409 are secured to the vertical wall parts 412, to produce a structurally simple, stable construction, while the bent-over longitudinal edges 409 moreover provide stiffening of the guide element 402. The further advantage thus achieved is that the guide elements 402 can also
5 be used without, for instance, support poles or the like, when relatively light material is used for the manufacture thereof. Thus, a hedge or comparable construction can be formed with such elements in an even simpler manner.

When different plant supports 410 are disposed side by side, as shown in Fig. 8, the bent-over longitudinal edges 409 of juxtaposed plant supports
10 410 can be intercoupled, for instance by binding means such as wire or tie wraps, to increase its stiffness. For that purpose, mirror symmetrical plant supports 410 can be used, as shown in Fig. 8 on the right-hand side, or identical plant supports, as shown in Fig. 8 on the left-hand side. Also, the longitudinal edges 409 of a guide element 402 can be bent over to the same
15 side, which may in particular be advantageous when relatively narrow box-shaped elements 401 are used. It will be understood that in other places, too, comparable bent-over portions can be provided in the guide element, with comparable stiffening effects.

Fig. 9 shows a portion of a box-shaped element 501 of a plant support
20 510 according to the invention, comparable with, for instance, Fig. 4. In this embodiment, the horizontal wires 508 and vertical wires 506, which together form the mesh-shaped structure as shown in Fig. 1, are incorporated into the covering material 520. The covering 520 is again composed as described with reference to Fig. 4. In this embodiment, the box-shaped element 501 is
25 preferably formed from a flat plate of mesh-shaped material which, before it is bent over, is covered on both sides with said covering material 520. For that purpose, the covering material 520 is pressed, glued or provided in another suitable manner around the mesh-shaped element. If necessary, the covering material can also be woven through the openings of the mesh-shaped element
30 or provided therethrough in another manner. After the provision of the

WO 00/76295

16

PCT/NL00/00411

covering 520, the element is subsequently bent over to form the box-shaped element 501, possibly after it has been cut to measure. However, it is also possible to fix the covering material 520 after bending of the box-shaped element 501. This manner of covering, wherein the mesh-shaped element is incorporated into the covering, offers the advantage of requiring fewer manufacturing operations, while, moreover, the mesh-shaped element is covered towards the outside.

It will be understood that the alternative embodiments shown in Figs. 7, 8 and 9 of at least parts of a plant support according to the invention can also be applied to the other exemplary embodiments shown, in the same or a similar manner.

Fig. 10 is a schematic side elevation of a noise protection wall 150, for instance for use along a road, railroad or the like. The noise protection wall 150 is built up from a number of regularly spaced apart trestles 152 secured in the ground 132. Against the trestles, on one or, as in the exemplary embodiment shown, both sides thereof, an apparatus 10, 110 according to the invention is placed, in an embodiment where a guide element 102 has only one side thereof provided with a box-shaped element 1, 101. Via the guide element, the apparatus 10, 110 is connected to the trestle 152, schematically represented by loops 154. The box-shaped elements 1, 101 can again be dug in in the ground 130, but may also be placed on a slope, schematically represented by 132. Digging in offers the advantage of providing a firmer construction. Next, between the trestles 152 and the guide elements 102, a filling material is provided, lava stone 156 in the embodiment shown. Lava stone absorbs noise in a particularly effective manner. Thus, a noise wall can be obtained in a particularly fast and simple manner, at relatively low costs. The elements 10, 110 used can have a relatively great height and length, for instance 3-5 m, enabling working fast. Since the roots 124 will grow to the outside of the box-shaped elements 1, 101, a firm anchoring is obtained, while, moreover, the vegetation will stay alive for a very long time. Thus, a well-

WO 00/6295

17

PCT/NL00/00411

overgrown noise wall is maintained, so that its noise-resistant, or at least the noise-absorbing features are increased even further.

The invention is in no way limited to the exemplary embodiments given in the specification and the Figures. Many variations thereof are possible within the framework of the invention.

Thus, the guide element can be positioned otherwise relative to the box-shaped element, for instance parallel to the longitudinal wall of the box-shaped element, while, moreover, the box-shaped element may also be constructed differently, for instance with diverging longitudinal walls. Both the box-shaped element and the guide element may be manufactured from other materials, for instance plastic, with openings formed otherwise, for instance perforated plate, while, moreover, one or more box-shaped elements may be directly formed from the material earlier described as covering material. It is further noted that as the case may be, hedge elements may also be formed without covering material, or with a different covering material, incapable of being grown through. Also, a hedge element according to the invention may be arch-shaped, with a box-shaped element on one or both sides of an arc element, for instance suitable for guiding roses. In principle, a plant support according to the invention may have any desired dimension. Thus, a hedge element shown in Figs. 1-3 has, for instance, a guide element whose size is about 2x2 m, but this may easily be adjusted to a user's wishes. Plant supports with or without guide element may be of a narrower design and provided with suitable coupling means, so that transportation is simplified, a greater freedom of design is realized and sufficient stability is maintained all the same. A plant support according to the invention can further be, for instance, bent, in top plan view as well as in side view.

These and many comparable variations are understood to fall within the framework of the invention as set out by the appended claims.

30-05-2001

A.34

WO 00/76295

PO-DG, NL 000000411

30.05.2001 PCT/NL00/00411

18

New set of Claims

(54)

1. A method for manufacturing a plant support, wherein a box-shaped element is manufactured having an at least partially open wall, the box-shaped element being at least partially covered with a preferably substantially biodegradable covering material, said covering material being provided in such a manner that it covers the partially open wall at least partially, such that the wall becomes soil-proof, while roots of a plant or the like, growing in the pot during use, can grow at least partially through the covering material and the wall to the outside of the plant support, characterized in that as covering material a material is manufactured from biodegradable material.
2. A method according to claim 1, wherein the box-shaped element is at least substantially manufactured from material having a mesh-shaped structure.
3. A method according to claim 1 or 2, wherein the box-shaped element is substantially manufactured from wire material.
4. A method according to any one of the preceding claims, wherein as covering material, a material is manufactured from natural materials, in particular from at least natural fibers and binding agent.
5. A method according to claim 4, wherein a covering material is used substantially built up from coco fibers and binding agent, in particular latex.
6. A method according to any one of the preceding claims, wherein from the covering material, a sheet-shaped element is taken which is folded into covering of the box-shaped element.
7. A method according to any one of the preceding claims, wherein the covering material is secured in the wall of the box-shaped element, in particular woven therein.
8. A method according to any one of the preceding claims, wherein a substantially vertically extending guide element is secured in or to the box-shaped element or formed integrally therewith, said guide element extending

AMENDED SHEET

30-05-2001

A.A.34

NL 000000411

19

above the surface of the box-shaped element and, during use, functioning as guide for plants and the like growing in the box-shaped element.

9. A method for cultivating plants and the like, utilizing a plant support manufactured by a method according to any one of the preceding claims,

- 5 wherein the box-shaped element is substantially disposed above the ground, such that the outer side of at least a longitudinal wall thereof is free, whereupon the box-shaped element is filled with soil and at least one plant or the like is planted therein, whereupon the or each plant is treated such that root growth occurs, partly extending also through the covering material, such
- 10 that the ends of a number of roots are located approximately in the outer face of the wall, while after sufficient growth of the plant, the plant support with the or each plant is picked up and moved to another position.

10. A method according to claim 9, wherein the plant support in said other position is secured in or to ground.

- 15 11. A method according to claim 10, wherein the plant support is dug in in the ground, such that roots of the or each plant grow outside through the plant support, into the ground, and provide for anchoring and nutrition.

12. A method according to claim 10, wherein the plant support is placed on ground, such that roots of the or each plant can grow through a bottom of the
- 20 plant support into the ground, for anchoring and nutrition.

13. A method for manufacturing a hedge, wherein a number of plant supports, each comprising at least one substantially vertically extending guide element along which at least one guidable plant is cultivated utilizing a method according to claim 9, are juxtaposed utilizing a method according to
- 25 claim 10 or 11, for forming a substantially closed, elongated hedge.

14. A method according to claim 13, wherein plants are guided on both sides of the at least one guide element, such that the at least one guide element is substantially entirely enclosed by the plants.

15. A hedge, at least a hedge element, manufactured by a method according
- 30 to claim 13 or 14.

3Q-05-2Q01 Art. 34

NL 000000411

20

16. A plant support, comprising a box element having an at least partially open wall, said wall being substantially covered with a covering material selected so that roots of a plant or the like placed in the plant support can grow through the covering material to the outside of the box-shaped element.
- 5 while soil poured into the box-shaped element substantially cannot pass the covering material, characterised in that as covering material a material is used manufactured from biodegradable material.
17. A plant support according to claim 16, wherein at least the box-shaped element is covered with a covering material which, during use, at least
- 10 temporarily prevents root growth to the outside of the box-shaped element.
18. A plant support according to claim 16 or 17, wherein the box-shaped element is covered with the covering material substantially on the inside, said covering material being in particular composed from substantially natural fibers and binding agent and having a relatively open structure.
- 15 19. A plant support according to any one of claims 16-18, wherein a guide element is provided which, during use, can extend substantially vertically and can be connected to the box-shaped element, for guiding plants or the like to be grown in the plant support.
20. A plant support according to claim 19, suitable and intended for use
- 20 with a method according to claim 13 or 14 or in a hedge according to claim 15.
21. A plant support according to claim 19 or 20, wherein the box-shaped element and the guide element are manufactured in one piece, preferably from mesh-shaped material such as woven wire metal.
22. A plant support according to any one of claims 16-20, wherein the plant
- 25 support is of demountable, or at least modular design.
23. A plant support according to claim 22, comprising a guide element, wherein at least one box-shaped element is provided which, by means of fasteners, is detachably mountable against the guide element, adjacent the bottom side thereof.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
21 December 2000 (21.12.2000)

PCT

(10) International Publication Number
WO 00/76295 A1

(51) International Patent Classification⁷: A01G 9/12, 23/04

(21) International Application Number: PCT/NL00/00411

(22) International Filing Date: 14 June 2000 (14.06.2000)

(25) Filing Language: Dutch

(26) Publication Language: English

(30) Priority Data:
1012317 14 June 1999 (14.06.1999) NL
1013842 14 December 1999 (14.12.1999) NL

(71) Applicant (for all designated States except US): DART-DIJK N.V. [NL/NL]; Chuchubiweg 17, Curacao (AN).

(72) Inventor; and

(75) Inventor/Applicant (for US only): JANSSEN, Henricus, Wilhelmus, Theodorus [NL/NL]; Hatertseweg 11a, NL-6581 KD Malden (NL).

(74) Agent: PRINS, A., W.; Vereenigde, Nieuwe Parklaan 97, NL-2587 BN The Hague (NL).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

- With international search report.
- Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PLANT SUPPORT AND METHOD FOR MANUFACTURING SUCH PLANT SUPPORT



(57) Abstract: A method for manufacturing a plant support, wherein a box-shaped element (1) is manufactured having an at least partially open wall, the box-shaped element (1) being at least partially covered with a preferably substantially biodegradable covering material (20), said covering material (20) being provided in such a manner that it covers the partially open wall at least partially, such that the wall becomes soil-proof, while roots of a plant or the like, growing in the pot during use, can grow at least partially through the covering material (20) and the wall to the outside of the plant support (1). Such plant supports (1) can be used to raise plants and the like at a first position and subsequently displacing them to a second, definitive position, where the plant supports (1) can be secured in or to the ground. The plant supports (1) can be provided with a substantially vertical guide element (2) along which a guide plant can be cultivated. By juxtaposing a number of said plant supports (1), a continuous hedge is obtained.

WO 00/76295 A1




Fig. 1




Fig. 2A




Fig. 2B




Fig. 2C




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10

**Declaration and Power of Attorney Patent Application
(Design or Utility)**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

Plant support and method for manufacturing such plant support

the specification of which

- ☐ is attached hereto *December 14, 2001 **10/018,115
☐ was filed on * as application serial no. ** and or PCT International
Application number PCT/NL00/00411 and was amended on (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to me to be material to patentability as defined in 37 C.F.R. §1.56.

I hereby claim foreign priority benefits under 35 U.S.C. §119(a)-(d) or 35 U.S.C. §365(b) of any foreign application(s) for patent or inventor's certificate, or 35 U.S.C. §365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate of PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)		
Number	Country	Day/Month/Year Filed
1012317	the Netherlands	14 June 1999
Number	Country	Day/Month/Year Filed
1013842	the Netherlands	14 december 1999
Number	Country	Day/Month/Year Filed

I hereby claim the benefit under 35 U.S.C. §119(e) of any United States provisional application(s) listed below:

Prior Provisional Application(s)	
Serial Number	Day/Month/Year Filing Date
Serial Number	Day/Month/Year Filing Date
Serial Number	Day/Month/Year Filing Date

I hereby claim the benefit under 35 U.S.C. §120 of any United States application(s), or under 35 U.S.C. §365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. §112, I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to me to be material to patentability as defined in 37 C.F.R. §1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application:

Prior U.S. or International Application(s)		
Serial Number	Day/Month/Year Filed	Status (patented, pending, abandoned)
Serial Number	Day/Month/Year Filed	Status (patented, pending, abandoned)
Serial Number	Day/Month/Year Filed	Status (patented, pending, abandoned)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements are made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. §1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Power of Attorney

As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

Attorney


Registration Number

Dana M. Raymond	18,540
Frederick C. Carver	17,021
Francis J. Hone	18,662
Joseph D. Garon	20,420
Arthur S. Tenser	18,839
Ronald B. Hildreth	19,498
Thomas R. Nesbitt, Jr.	22,075
Robert Neuner	24,316
Richard G. Berkely	25,465
Richard S. Clark	26,154
Bradley B. Geist	27,551
James J. Maune	26,946
John D. Murnane	29,836
Henry Tang	29,705
Robert C. Scheinfeld	31,300
John A. Fogerty, Jr.	22,348
Louis S. Sorell	32,439
Rochelle K. Seide	32,300
Gary M. Butler	33,841
Marta E. Delsignore	32,689
Lisa B. Kole	35,225

I hereby authorize them or others whom they may appoint to act and rely on instructions from and communicate directly with the person/organization who/which first sends this case to them and by whom/which I hereby declare that I have consented after full disclosure to be represented unless/until I instructed otherwise.

Please direct all correspondence in this case to at the address indicated below:

BAKER BOTTS, L.L.P.
30 Rockefeller Plaza
New York, New York 10112
United States of America

Full Name of Sole or First Inventor		
Family Name <u>Janssen</u>	First Given Name <u>Henricus</u>	Second Given Name <u>Wilhelmus Theodorus</u>
Residence and Citizenship		
City of Residence <u>Malden</u>	State or Country of Residence <u>the Netherlands</u>	Country of Citizenship <u>the Netherlands</u>
Post Office Address		
Street Address <u>Hatertseweg 11a</u>	City <u>Malden</u>	State & Zip Code or Country <u>6581 KD</u>
Signature of Inventor 		Date <u>5-06-2002</u>